

# FreeStyle™ Maintenance

## In General

FreeStyle is a durable, relatively low maintenance product. Actual maintenance requirements will depend on the volume and type of traffic on your floor. Color and style will also effect maintenance requirements. In general, darker colors tend to show scratches, scuffs, dirt and general wear, whereas lighter colors tend to show dark marks and stains more easily.

FreeStyle's heavy-duty wear layer is designed to be tough but it is not indestructible and it will scratch and scuff when subjected to harsh conditions or sharp objects. To minimize the impacts of dirt and abrasion from daily traffic use non-staining walk-off mats in door and entry-ways wherever possible.

## Initial/Daily Maintenance

1. Sweep or vacuum the flooring to remove loose grit or debris and wipe clean with a damp mop.
2. Post "Wet Floor" signs.
3. Thoroughly clean floor using Johnsonite Stride™, GP Forward™ or equal, following label instructions.
4. Use red pad or mop for initial and daily maintenance.
5. **NEVER USE A BLACK OR BROWN PAD ON A FREESTYLE FLOOR.**
6. Pick up any leftover cleaning solution with wet/dry vacuum, auto scrubber, or mop.
7. Allow to dry thoroughly.

## Spray Buffing – Using 175 r.p.m. machine and appropriate spray buff pad. **(DO NOT USE HIGH SPEED BUFFER)**

1. Sweep and/or dust mop the floor daily to remove surface dirt.
2. Post "Wet Floor" signs.
3. Damp mop or auto scrub using **STRIDE™** or **GP FORWARD™**, according to label directed use. Spray a light mist of **SNAPBACK™** Floor Maintainer to a small area and buff using a red spray buff pad. Equivalent products may be substituted.
4. Be sure the floor is clean and dry before starting this procedure.

## CAUTION!!!

- **Always clean floor before buffing. Do not buff a dirty floor.**
- **Turn pad often to prevent build up.**
- **Do not buff in one place too long, as burn marks may occur.**

**NOTE: These maintenance products are not intended for consumer use. Commercial use only.**