

SelecTile Flooring™

Industrial Interlocking Flooring System



SELECTILE MAKES INSTALLATION A SNAP

SelecTile vinyl floor tiles are made using recycled PVC materials and have a unique interlocking edge design to eliminate the need for adhesives, making installation quick and inexpensive. Non-porous, flexible and durable, SelecTile remains in-place even with heavy traffic and abuse. It can be installed directly over damaged or problem floors with minimal subfloor prep, is resistant to most solvents, chemicals and abrasion, and is easy to maintain, reconfigure or remove.


SELECTILE IS BUILT FOR TOUGH ENVIRONMENTS

SelecTile is designed for use in heavy-duty, high-traffic industrial, manufacturing, institutional, transportation, shipping, warehouse and similar areas. It withstands point-loads of up to 1,000 p.s.i., including forklifts, pallet jacks, carts and other wheeled conveyances and requires minimal maintenance.



PATTERNS AND COLORS

SelecTile Industrial is available in smooth, coin and diamond surfaces in seven standard colors. For custom colors, contact SelecTech for minimum order quantity requirements.



Red



Blue



Green



Brown



Gray



Black



LEED™

by SelecTech

Made in USA

www.freestyleflooring.com

SelecTile Flooring Specifications

CONSTRUCTION

Dimensions (finished surface)	23.75" x 23.75" 60.3 cm x 60.3 cm
Coverage	3.92 sq ft/tile 0.36 sq meter/tile
Thickness	0.22" 5.6 mm
Weight	6.0 lbs/tile

PERFORMANCE CHARACTERISTICS

Noise Reduction	Excellent
Underfoot Comfort	Superior
Stain Resistance	Excellent
Maintenance	No Wax
Made in USA	
Warranty	10-Year Commercial

LEED Use of FreeStyle flooring can contribute to points in Materials and Resources, Regional Materials, Indoor Environmental Quality, and Innovation Credit categories. For more details, see LEED insert or visit www.freestyleflooring.com.

ARCHITECTURAL SPECIFICATIONS - Short Form

Go to www.freestyleflooring.com for complete CSI-format Architectural Specifications.

All floors as indicated in the Finish Schedule or listed in this specification shall be SelecTile Resilient Flooring, manufacture by SelecTech, Inc. Avon, MA, color code (insert color code). SelecTiles shall be made from at least 20% recycled materials. The product shall be an interlocking floor tile and be available in 23.75" x 23.75" (60.3 cm x 60.3 cm) squares and with a thickness of 0.22 inches (5.6mm). The product shall offer a 10-year Limited Warranty against wear as detailed in the SelecTile Warranty brochure. Tiles shall be installed as a free-lay product without adhesives. Installation shall be as recommended in the SelecTile Installation Guide.

Installation All SelecTech flooring products are interlocking floor tiles. SelecTiles cover 23.75" x 23.75" or 3.92 square feet per tile. Due to the large tile size, use a waste/contingency factor of between 3% and 5% when estimating a job. A plastic deadblow mallet should be used for joining tiles. Use of a vinyl tile cutting tool or saw is required for cutting around obstacles. All SelecTech flooring products are free-lay systems that do not require adhesives and may be installed over concrete, wood, asbestos tile, rubber, vinyl composite tiles and other standard floors. A 1/4" (6.35 mm) gap around the perimeter should be left to allow for expansion and contraction. See SelecTile Installation Guides or go to www.freestyleflooring.com for additional instructions.

Maintenance SelecTech flooring products can be cleaned with neutral or other readily available cleaners using a mop or sponge or with a power scrubber or buffer equipped with a white pad. See SelecTile Maintenance Guide or go to www.freestyleflooring.com for additional instructions.

Warranties SelecTech flooring products are backed by a 10-year limited warranty against wear and a one-year warranty against manufacturing defects. *Unlike many other flooring products, warranties on SelecTech flooring products are NOT VOIDED because of problems caused by moisture and hydrostatic pressure in the subfloor; or by buyer's failure to use manufacturer's specified adhesive.* See www.freestyleflooring.com for warranty details.

PHYSICAL PROPERTIES

Abrasion Resistance	<0.01 gram weight loss ASTM D-3389
Coefficient of Friction	0.70
Conforms to ADA Recommendations	ASTM D-2047
Critical Radiant Flux	>0.45 watts/cm ²
Meets Class I Fire Rating	ASTM E-648
Smoke Density	≤450 ASTM E-662
Static Load Resistance	1000 psi ASTM F-970

ENVIRONMENTAL QUALITY

Recycled Content	20% (min. 50% post-consumer)
Air Quality	CA Prop. 1350 IEQ Protocol
Meets Requirement for LEED IEQ 4.3	
Quality System	ISO 9001