

FreeStyleTM is Good For the Soles!

FreeStyleTM Interlocking Environmental Flooring is a great choice for Retail Stores. With a durable wear layer, it's built for the demanding requirements of a retail setting. It installs quickly, without glues, and can be used immediately upon installation. Since it doesn't need glues, it's easy to move if the store is reconfigured and won't be prone to the failures commonly found with conventional glue-down flooring, thereby making it a safer choice with lower ongoing maintenance costs. Made in a variety of attractive styles, it can be installed directly over old flooring and can be walked on immediately, eliminating the typical downtime and disruption found with conventional glue-down flooring products. Best of all, FreeStyleTM is made from recycled materials – it's good for the soles and the environment! In retail stores, FreeStyleTM has a number of distinct advantages:

Solves Problems

- Can Be Used Directly On Top of Old Flooring
- Covers High Moisture Concrete
- No Adhesive Failures to Worry About

Quick Installation

- Reduces Downtime
- Meets "Quick Build" Timelines
- Don't Have to Wait for New Concrete to Fully Cure
- Use Floor Immediately After Installed
- Easily Installed and Changed to Suit Changing Promotional Needs
- Damaged Tiles Can Be Changed Easily and Quickly

Durability to Match the Most Demanding Environments

- Formulated for High Traffic and Commercial Use
- 10-Year Commercial Wear Through Warranty

Resilient Construction for Safety and Comfort

- Reduces Noise
- Meets ADA Requirements for Slip Resistance
- Better Comfort Under Foot

Environmentally Preferred

- Made with 50% Recycled Materials, Including Post-Consumer Carpeting
- 100% Recyclable Back into New FreeStyle - We'll Take it Back!
- Portable for Re-use
- Interlocking to Eliminate the VOCs from Adhesives



"Our mission is to encourage consumers to appreciate the outdoors and the responsibility that accompanies this privilege. We wanted a 'green' flooring material that would be comfortable to walk on, install and maintain easily, and be reliable. FreeStyle helped us meet all of these needs."



Eastern Mountain Sports



Eastern Mountain Sports wanted an attractive and comfortable floor for its shoe department to provide customers with the proper setting for selecting new shoes. FreeStyle flooring, with its patented resilient composition, provided the perfect solution. Better still, there were no installation hassles and no waiting for concrete to cure and adhesives to dry. FreeStyle was simply snapped together, directly on the concrete subfloor, and ready to use immediately, which helped make the whole build-out project run more smoothly.



Freestyle Interlocking Flooring

Limited 10-Year Warranty

FreeStyle™ is manufactured to provide a durable and long-lasting floor covering under a range of temperature and exposure conditions and is backed by a 10-Year Limited Warranty against wear. Ask your FreeStyle™ dealer for more details on this Limited 10-Year Warranty.

Installation

FreeStyle™ is a 18.5" x 18.5" (2.38 sq. ft./tile) inter-locking floor tile. A plastic tipped mallet or deadhead hammer should be used for joining these products. Tiles can be cut using a utility knife, vinyl-tile cutter, or jig saw. FreeStyle™ is a free-lay system and does not require the use of adhesives. FreeStyle™ may be installed over concrete, wood, asbestos tile, rubber, vinyl, composite tiles, and other standard floors. A 3/8" gap around the perimeter should be left to allow for expansion and contraction. For more detailed instructions, consult the FreeStyle™ Installation Guide.

Regular Maintenance

FreeStyle™ is easy to clean and maintain. The tiles can be cleaned with standard neutral cleansers or other acceptable cleansers. The tiles can be cleaned by hand using a mop or sponge. A power scrubber or buffer can also be used to clean particularly tough stains and soiling.

Architectural Specifications


All floors shown in the Finish Schedule or listed in this specification shall be FreeStyle™ Resilient Flooring, manufactured by SelecTech, Inc. Avon, MA. The product shall be an interlocking floor tile and be available in 18.5" x 18.5" squares (nominal) and with a thickness of 0.375 inches. The product shall offer a 10-Year Limited Warranty against wear as detailed in the FreeStyle™ Warranty brochure. The tiles shall be installed as a free-lay product without adhesives. Installation shall be as recommended in the FreeStyle™ Installation Guide.

For more information contact:

SelecTech, Inc.
33 Wales Ave, Unit F, Avon, MA 02322
Phone: 508-583-3280

Visit our website at www.freestyleflooring.com

Physical Properties

Dimensions	18.5" x 18.5" x 0.375"
Thickness	0.375"
Effective Coverage	2.38 square feet per tile
Weight	5.2 lbs per tile
Reference Specification ASTM F-1700	Conforms
Critical Radiant Flux ASTM E-648	> 1.0 W/cm ² Meets Class I Fire Rating
Smoke Density ASTM E-662	≤ 450
Chemical Resistance ASTM F-925	Excellent resistance to Acids, Alkalis, Household Chemicals
Recycled Content 	50%

Solvent/Stain Resistance

FreeStyle™ has been tested for solvent/stain resistance per ASTM F-925-96 against a number of fluids, such as oils, acids, solvents, and staining agents.

SelecTech has pioneered advanced, state-of-the-art solutions to produce environmentally-friendly, high-performance commercial products. As the first U.S. company to produce such products from hard-to-recycle scrap plastic, SelecTech uses its patented technologies and proprietary process to solve environmental waste problems that other companies can't.

