



## Just What The Doctor Ordered!

For busy hospitals and clinics with tight downtime constraints, **FreeStyle™** Interlocking Environmental Flooring is the perfect flooring solution. Installed directly over old flooring, with no need for adhesives, it can be walked on immediately, eliminating the typical disruptions found with conventional glue-down flooring products. No need for concrete to fully cure and no need for glue to dry! It has a durable wear layer, so it can stand up to heavy traffic. **FreeStyle™** is available in many attractive styles, is made from recycled materials, and has a stain-resistant composition.

In hospitals and clinics, **FreeStyle™** offers:

**Solves Problems**

- Can Be Installed over Problem Sub-Floors
- Covers High Moisture Concrete
- No Adhesive Failures to Worry About

**Quick Installation**

- Meets "Quick Build" Timelines
- Installs directly over Existing Floors / Eliminates wait
- Floor Can Be Used Immediately After Installation
- Eliminates Costly and Disruptive Rip-Out of Old Flooring
- Damaged Tiles Can Be Changed Easily and Quickly

**Durability to Match the Most Demanding Environments**

- Waterproof, Anti-Microbial, & Chemical & Stain-Resistant
- Formulated for High Traffic and Commercial Use
- 10-Year Commercial Wear Through Warranty

**Resilient Construction for Safety and Comfort**

- Better Comfort Under Foot
- Reduces Noise
- Meets ADA Requirements for Slip Resistance

**Environmentally Preferred**

- Made with 50% Recycled Materials and Portable for Re-Use
- 100% Recyclable Back into New FreeStyle - We'll Take it Back!
- Interlocking to Eliminate the VOCs from Adhesives

*"Our mission is to provide the best possible care for families throughout Western New York and beyond. So when we were upgrading many of the units here, it was imperative that we minimize the interruption to our staff and patients. The removal of the old flooring would have required closing units. When we found **FreeStyle™** flooring and learned that it could be put directly over the old problem floor, we knew we had our solution."*



## Kaleida Women & Children's Hospital



When Kaleida Women's and Children's Hospital replaced its floors, they needed flooring that could be installed with minimal downtime. They also wanted a "Green" floor — one that would be comfortable to walk on and in a style consistent with the designer's vision. With **FreeStyle™**, the hospital's maintenance crew was able to install directly over the existing ceramic floor quickly and cost effectively. To match the décor, a custom color was created and now they have a gorgeous, comfortable, environmentally friendly floor!



## Limited 10-Year Warranty

**FreeStyle™** is manufactured to provide a durable and long lasting floor covering under a range of temperature and exposure conditions and is backed by a 10-Year Limited Warranty against wear. Ask your **FreeStyle™** dealer for more details on this Limited 10-Year Warranty.

## Installation

**FreeStyle™** is a 18.5" x 18.5" (2.38 sq. ft./tile) interlocking floor tile. A plastic tipped mallet or deadhead hammer should be used for joining these products. Tiles can be cut using a utility knife, vinyl-tile cutter, or jig saw. **FreeStyle™** is a free-lay system and does not require the use of adhesives. **FreeStyle™** may be installed over concrete, wood, asbestos tile, rubber, vinyl, composite tiles, and other standard floors. A 3/8" gap around the perimeter should be left to allow for expansion and contraction. For more detailed instructions, consult the **FreeStyle™** Installation Guide.

## Regular Maintenance

**FreeStyle™** is easy to clean and maintain. The tiles can be cleaned with standard neutral cleansers or other acceptable cleansers. The tiles can be cleaned by hand using a mop or sponge. A power scrubber or buffer can also be used to clean particularly tough stains and soiling.

## Architectural Specifications

All floors shown in the Finish Schedule or listed in this specification shall be **FreeStyle™** Resilient Flooring, manufactured by SelecTech, Inc. Avon, MA. The product shall be an interlocking floor tile and be available in 18.5" x 18.5" squares (nominal) and with a thickness of 0.375 inches. The product shall offer a 10-Year Limited Warranty against wear as de- tailed in the **FreeStyle™** Warranty brochure. The tiles shall be installed as a free-lay product without adhesives. Installation shall be as recommended in the **FreeStyle™** Installation Guide.

## Solvent/Stain Resistance

**FreeStyle™** has been tested for solvent/stain resistance per ASTM F-925-96 against a number of fluids, such as oils, acids, solvents, and staining agents.

Physical Properties	
<b>Dimensions</b>	18.5" x 18.5" x 0.375
<b>Thickness</b>	0.375"
<b>Effective Coverage</b>	2.38 square feet per tile
<b>Weight</b>	5.2 lbs per tile
<b>Critical Radiant Flux</b> ASTM E-648	> 1.0 W/cm <sup>2</sup> Meets Class I Fire Rating
<b>Smoke Density</b> ASTM E-662	≤ 450
<b>Reference Specification</b> ASTM F-1700	Conforms
<b>Chemical Resistance</b> ASTM F-925	Excellent resistance to Acids, Alkalis, Household Chemicals
<b>Recycled Content</b>	50%

**SelecTech has pioneered advanced, state-of-the-art solutions to produce environmentally-friendly, high-performance commercial products. As the first U.S. company to produce such products from hard-to-recycle scrap plastic, SelecTech uses its patented technologies and proprietary process to solve environmental waste problems that other companies can't.**

### For more information contact:

StaticStop (a division of SelecTech, Inc.)  
 33 Wales Ave, Unit F, Avon, MA. 02322  
 Phone: (877) 738-4537  
 E-mail: [info@staticstop.com](mailto:info@staticstop.com)  
 Visit our ESD website at [www.StaticStop.com](http://www.StaticStop.com)