

FreeStyle for a Speedy Recovery!

For busy medical laboratories, **FreeStyle™** Interlocking Environmental Flooring is just what the doctor ordered! By completely eliminating the need for any adhesive, it can be walked on immediately upon installation. **FreeStyle™** installs quickly and radically reduces the typical downtime and disruption found with conventional glue-down flooring products. And its flexible composition means it can be installed directly over old flooring! **FreeStyle™** has durable wear layer made to handle heavy traffic. It's available in a large selection of attractive styles and is stain-resistant and anti-microbial.

In medical laboratories **FreeStyle™** cures what ails your floors by offering:

Solves Problems

- Can Be Installed over Old Flooring
- Covers High Moisture Concrete
- No Adhesive Failures to Worry About

Quick Installation

- Meets "Quick Build" Timelines
- No Wait for New Concrete to Fully Cure
- Floor Can Be Used Immediately After Installation
- Easily Installed and Changed to Suit Changing Promotional Needs
- Damaged Tiles Can Be Changed Easily and Quickly

Durability to Match the Most Demanding Environments

- Waterproof, Anti-Microbial, & Chemical & Stain-Resistant
- Formulated for High Traffic and Commercial Use
- 10-Year Commercial Wear Through Warranty

Resilient Construction for Safety and Comfort

- Better Comfort Under Foot
- Reduces Noise
- Meets ADA Requirements for Slip Resistance

Environmentally Preferred

- Made with 50% Recycled Materials
- 100% Recyclable Back into New FreeStyle - We'll Take it Back!
- Glue-free Installation to Eliminate the VOCs from Adhesives

BC Biomedical



When BC Biomedical Laboratories needed to replace their floor due to moisture failure, they needed a free-floating floor that would resist moisture, feel comfortable underfoot, and install quickly. **FreeStyle™** was exactly what they needed and has become their standard flooring for all installations directly on slab. And because **FreeStyle™** is available in a variety of colors and designs, it can be matched to the existing color scheme in each BC Biomedical location.



*"At BC Biomedical, we make a commitment to deliver uncompromising service to our customers. **FreeStyle™** has helped us keep that commitment by installing quickly, resulting in less disruptions. We also strive to be a great place to work, and **FreeStyle™** helps there too, by being so comfortable to walk and stand on".*



Limited 10-Year Warranty

FreeStyle™ is manufactured to provide a durable and long lasting floor covering under a range of temperature and exposure conditions and is backed by a 10-Year Limited Warranty against wear. Ask your **FreeStyle™** dealer for more details on this Limited 10-Year Warranty.

Installation

FreeStyle™ is a 18.5" x 18.5" (2.38 sq. ft./tile) interlocking floor tile. A plastic tipped mallet or deadhead hammer should be used for joining these products. Tiles can be cut using a utility knife, vinyl-tile cutter, or jig saw. **FreeStyle™** is a free-lay system and does not require the use of adhesives. **FreeStyle™** may be installed over concrete, wood, asbestos tile, rubber, vinyl, composite tiles, and other standard floors. A 3/8" gap around the perimeter should be left to allow for expansion and contraction. For more detailed instructions, consult the **FreeStyle™** Installation Guide.

Regular Maintenance

FreeStyle™ is easy to clean and maintain. The tiles can be cleaned with standard neutral cleansers or other acceptable cleansers. The tiles can be cleaned by hand using a mop or sponge. A power scrubber or buffer can also be used to clean particularly tough stains and soiling.

Architectural Specifications

All floors shown in the Finish Schedule or listed in this specification shall be **FreeStyle™** Resilient Flooring, manufactured by SelecTech, Inc. Avon, MA. The product shall be an interlocking floor tile and be available in 18.5" x 18.5" squares (nominal) and with a thickness of 0.375 inches. The product shall offer a 10-Year Limited Warranty against wear as detailed in the **FreeStyle™** Warranty brochure. The tiles shall be installed as a free-lay product without adhesives. Installation shall be as recommended in the **FreeStyle™** Installation Guide.

Solvent/Stain Resistance

FreeStyle™ has been tested for solvent/stain resistance per ASTM F-925-96 against a number of fluids, such as oils, acids, solvents, and staining agents.

Physical Properties	
Dimensions	18.5" x 18.5"
Thickness	0.34"
Effective Coverage	2.38 square feet per tile
Weight	5.2 lbs per tile
Critical Radiant Flux ASTM E-648	> 1.0 W/cm ² Meets Class I Fire Rating
Smoke Density ASTM E-662	≤ 450
Reference Specification ASTM F-1700	Conforms
Chemical Resistance ASTM F-925	Excellent resistance to Acids, Alkalis, Household Chemicals
Recycled Content	50%

SelecTech has pioneered advanced, state-of-the-art solutions to produce environmentally-friendly, high-performance commercial products. As the first U.S. company to produce such products from hard-to-recycle scrap plastic, SelecTech uses its patented technologies and proprietary process to solve environmental waste problems that other companies can't.

For more information contact:

StaticStop (a division of SelecTech, Inc.)
 33 Wales Ave, Unit F, Avon, MA. 02322
 Phone: (877) 738-4537
 E-mail: info@staticstop.com
 Visit our ESD website at www.StaticStop.com