

FreeStyle™ is the Fresh Choice in Supermarkets and Grocery Stores!

FreeStyle™ Interlocking Environmental Flooring meets the demanding needs of supermarkets and grocery stores. Made in a variety of attractive styles, it can be installed directly over old flooring and can be walked on immediately, thereby eliminating the typical downtime and disruption experienced with conventional glue-down flooring products.

In supermarkets and grocery stores, **FreeStyle™** has a number of distinct advantages:

Solves Problems

- Can Be Installed over Old Flooring
- Covers High Moisture Concrete

Quick Installation

- Meets "Quick Build" Timelines
- Floor Can Be Used Immediately After Installation
- Easily Installed and Changed to Suit Changing Promotional Needs
- Damaged Tiles Can Be Changed Easily and Quickly

Durability to Match the Most Demanding Environments

- Formulated for High Traffic and Commercial Use
- 10-Year Commercial Wear Through Warranty

Resilient Construction for Safety and Comfort

- Better Comfort Under Foot
- Reduces Noise
- Meets ADA Requirements for Slip Resistance



"The floor we had was super-nasty with breaking tiles and moisture problems. The quote we got to tear out the old flooring and repair the existing subfloor was very high. FreeStyle was much less expensive and a heck of a lot easier."



Daniel's Market



Daniel's Market in Santa Rosa, CA needed to replace a deteriorating floor with something attractive. Their old VCT floor was failing due to subfloor moisture problems, and was ugly and unsafe. But, they couldn't afford the costs associated with rip out, floor-prep, replacement, and downtime.

FreeStyle™ more than met their needs.

It was installed directly over the old flooring during the market's off-hours and without any disruption to store business. The end result was a beautiful and durable floor without a moment of lost business.



Limited 10-Year Warranty

FreeStyle™ is manufactured to provide a durable and long lasting floor covering under a range of temperature and exposure conditions and is backed by a 10-Year Limited Warranty against wear. Ask your **FreeStyle™** dealer for more details on this Limited 10-Year Warranty.

Installation

FreeStyle™ is a 18.5" x 18.5" (2.38 sq. ft./tile) interlocking floor tile. A plastic tipped mallet or deadhead hammer should be used for joining these products. Tiles can be cut using a utility knife, vinyl-tile cutter, or jig saw. **FreeStyle™** is a free-lay system and does not require the use of adhesives. **FreeStyle™** may be installed over concrete, wood, asbestos tile, rubber, vinyl, composite tiles, and other standard floors. A 3/8" gap around the perimeter should be left to allow for expansion and contraction. For more detailed instructions, consult the **FreeStyle™** Installation Guide.

Regular Maintenance

FreeStyle™ is easy to clean and maintain. The tiles can be cleaned with standard neutral cleansers or other acceptable cleansers. The tiles can be cleaned by hand using a mop or sponge. A power scrubber or buffer can also be used to clean particularly tough stains and soiling.

Architectural Specifications

All floors shown in the Finish Schedule or listed in this specification shall be **FreeStyle™** Resilient Flooring, manufactured by SelecTech, Inc. Avon, MA. The product shall be an interlocking floor tile and be available in 18.5" x 18.5" squares (nominal) and with a thickness of 0.34 inches. The product shall offer a 10-Year Limited Warranty against wear as detailed in the **FreeStyle™** Warranty brochure. The tiles shall be installed as a free-lay product without adhesives. Installation shall be as recommended in the **FreeStyle™** Installation Guide.

Solvent/Stain Resistance

FreeStyle™ has been tested for solvent/stain resistance per ASTM F-925-96 against a number of fluids, such as oils, acids, solvents, and staining agents.

Physical Properties

Dimensions	18.5" x 18.5"
Thickness	0.34"
Effective Coverage	2.38 square feet per tile
Weight	5.2 lbs per tile
Critical Radiant Flux ASTM E-648	> 1.0 W/cm ² Meets Class I Fire Rating
Smoke Density ASTM E-662	≤ 450
Reference Specification ASTM F-1700	Conforms
Chemical Resistance ASTM F-925	Excellent resistance to Acids, Alkalis, Household Chemicals
Recycled Content	50%

SelecTech has pioneered advanced, state-of-the-art solutions to produce environmentally-friendly, high-performance commercial products. As the first U.S. company to produce such products from hard-to-recycle scrap plastic, SelecTech uses its patented technologies and proprietary process to solve environmental waste problems that other companies can't.

For more information contact:

StaticStop (a division of SelecTech, Inc.)
33 Wales Ave, Unit F, Avon, MA. 02322
Phone: (877) 738-4537
E-mail: info@staticstop.com
Visit our ESD website at www.StaticStop.com