

FREESTYLE CHOICE

SELECTECH FREESTYLE FLOORING MADE WITH TPE AND BIO-BASED
POLYURETHANE

COMMERCIAL INTERLOCKING FLOORING

Made with TPE and bio-based polyurethane

SelecTech makes installing a new flooring system quick and easy. With minimal subfloor preparation and no need for adhesives, our tiles can be placed directly over irregular or high moisture subfloors. Maintenance is just as simple. Our tiles have excellent stain resistance, and have a urethane, no-wax finish.

KEY BENEFITS

- Patented, glueless, "zipper" interlock
- Low installation cost
- Flexible underlayment
- Designed for commercial applications
- 100% waterproof
- No chlorine or halogens
- 80% rapidly renewable content
- Dense, closed-top surface for easy maintenance



SPECIFICATIONS

Construction

Dimensions (finished surface)	18.5" x 18.5" 47.0cm x 47.0cm
Coverage	2.38 sq ft/file 0.22 sq meter/tile
Thickness	0.34" 7.9mm
Commercial Wear Surface	20 mil (0.5 mm) Ceramic/Urethane Wear Coat
Weight	5.2 lbs/tile

Physical Properties

Abrasion Resistance:	<0.01 gram weight loss ASTM D-3389
Coefficient of Friction Conforms to ADA Recommendations	0.92 ASTM D-2074
Critical Radiant Flux Meets Class I Fire Rating	>0.45 watts/cm ² ASTM E-648
Smoke Density	≤450 ASTM E-662

Performance Characteristics

Noise Reduction	Excellent
Underfoot Comfort	Superior
Stain Resistance	Excellent
Maintenance	No Wax
Warranty	10-Year Commercial

**No Adhesive. No Special
Tools. No Special Skills**

PLACE FreeStyle



LOCK SEAM using a mallet

